

Sales Data Sheet

Norafin 

  EXTRA ORGANIC
A Brand of Norafin

NAME

DESCRIPTION

TYPE

COMPOSITION

SURFACE

Fire Rating
(applied to the wall)*

DIN EN 13501

B-s1,d0

CE Certification

EN 15102:2007+A1:2011



COV Emission

DIN ISO 16000-3/-6/-9/-11

A+

Sound Absorbtion Rate

DIN EN ISO 10534

Applied to the wall

DIN EN ISO 354:2003

20 mm distance to the wall

Printing Profiles

Canon Colorado
HP Latex

UVgel certified
Profiled only

PROPERTY	DIRECTION	TEST METHOD	UNITS	VALUES
Weight			g/m ²	
Thickness			mm	
Tensile strength	MD		N/5 cm	
	CD		N/5 cm	
Elongation at break	MD		%	
	CD		%	
Air permeability @ 200 Pa			l/dm ² /min	

* FR-Version for other application available as item 01784.99

Disclaimer: The data are based on the determination and measurements of virgin fabrics and are subject to usual tolerances. This information does not express or imply any guarantee and the right is reserved to make any alterations without notice.

Please get in touch for specific finishing! Our products can be enhanced with a textile backing, surface coating, self-adhesive function or a print primer.



STANDARD 100
16.0.90034
Hohenstein HTTI
www.oeko-tex.com



Norafin Industries (Germany) GmbH
Gewerbegebiet Nord 3 | 09456 Mildenau
Tel. +49 3733 5507 0
info@norafin.com
www.norafin.de